

TABLE 2: Eau Claire: Summary of Significant Drill Results

July 27, 2017

| Type        | Drill Hole | From<br>(m) | To<br>(m) | Interval<br>(m) <sup>(1)</sup> | Gold Assay<br>(g/t Au) <sup>(2)</sup> | Vertical<br>Depth (m) <sup>(3)</sup> | Zone     |
|-------------|------------|-------------|-----------|--------------------------------|---------------------------------------|--------------------------------------|----------|
| Infill      | ER17-753   | 23.5        | 24.0      | 0.5                            | 1.45                                  | 17                                   | 850W     |
|             |            | 28.1        | 38.0      | 9.9                            | 1.11                                  | 26                                   |          |
|             |            | incl. 37    | 38.0      | 1.0                            | 3.26                                  |                                      |          |
| exploration | ER17-765   | 209.3       | 209.8     | 0.5                            | 1.92                                  | 156                                  | SL fence |
|             |            | 268.5       | 269.0     | 0.5                            | 2.95                                  | 97                                   |          |
| exploration | ER17-767   | 97.65       | 98.65     | 1.0                            | 1.52                                  | 65                                   | SL fence |
| exploration | ER17-751   | 274.0       | 275.0     | 1.0                            | 2.50                                  | 206                                  | 450W     |
| exploration | ER17-768   | 63.5        | 64.5      | 1.0                            | 1.29                                  | 52                                   | 850W     |
|             |            | 377.0       | 377.5     | 0.5                            | 3.21                                  | 309                                  |          |
|             |            | 382.5       | 383.0     | 0.5                            | 6.80                                  | 313                                  |          |
|             |            | 510.5       | 511.5     | 1.0                            | 4.28                                  | 418                                  |          |
| exploration | ER17-761   | 20.0        | 20.5      | 0.5                            | 2.44                                  | 15                                   | 450W     |
| Deep Swarm  | ER17-772   | 242.0       | 243.2     | 1.2                            | 1.02                                  | 225                                  | 450W     |
|             |            | 493.5       | 494.5     | 1.0                            | 1.24                                  | 451                                  |          |
|             |            | 607.0       | 608.0     | 1.0                            | 1.06                                  | 551                                  |          |
|             |            | 632.0       | 633.0     | 1.0                            | 1.52                                  | 573                                  |          |
|             |            | 641.0       | 642.0     | 1.0                            | 1.01                                  | 581                                  |          |
| Deep Swarm  | ER17-774   | 132.5       | 134.0     | 1.5                            | 1.50                                  | 125                                  | 450W     |
|             |            | 273.0       | 274.0     | 1.0                            | 1.01                                  | 257.5                                |          |
|             |            | 391.0       | 392.0     | 1.0                            | 1.40                                  | 367                                  |          |
|             |            | 570.5       | 574.6     | 4.1                            | 30.8                                  | 529                                  |          |
| HGS         | ER17-776   | 172.0       | 172.5     | 0.5                            | 21.3                                  | 127                                  | 450W     |
|             |            | 204.2       | 205.0     | 0.8                            | 1.02                                  | 150                                  |          |
|             |            | 229.1       | 230.6     | 1.5                            | 2.36                                  | 169                                  |          |
|             |            | 235.1       | 238.7     | 3.6                            | 2.85                                  | 174                                  |          |
|             |            | incl. 235.1 | 237.1     | 2.0                            | 4.24                                  |                                      |          |
|             |            | 242.2       | 243.8     | 1.6                            | 1.09                                  | 178                                  |          |
|             |            | 245.3       | 245.8     | 0.5                            | 1.10                                  | 180                                  |          |
|             |            | 260.8       | 265.3     | 4.5                            | 6.25                                  | 193                                  |          |
|             |            | incl. 261.8 | 263.3     | 1.5                            | 9.36                                  |                                      |          |
|             |            | 291.0       | 297.0     | 6.0                            | 15.3                                  | 215                                  |          |
|             |            | incl. 291.0 | 293.0     | 2.0                            | 41.6                                  |                                      |          |
|             |            | 318.3       | 326.6     | 8.3                            | 3.98                                  | 236                                  |          |
|             |            | incl. 318.3 | 320.8     | 2.5                            | 8.70                                  |                                      |          |
|             |            | 345.2       | 381.0     | 35.8                           | 7.09                                  | 265                                  |          |
|             |            | incl. 353.8 | 367.5     | 13.7                           | 9.23                                  |                                      |          |
|             |            | and 360.3   | 363.8     | 3.5                            | 19.5                                  |                                      |          |
|             |            | incl. 370.5 | 372.0     | 1.5                            | 12.8                                  |                                      |          |
| incl. 373.5 | 378.0      | 4.5         | 8.65      | 335                            |                                       |                                      |          |
| 458.0       | 459.0      | 1.0         | 2.05      |                                |                                       |                                      |          |
| 478.5       | 479.5      | 1.0         | 3.75      |                                | 350                                   |                                      |          |
| Infill      | ER17-704   | 14.8        | 17.5      | 2.7                            | 1.00                                  | 26                                   | 450W     |
|             |            | 119.4       | 122.7     | 3.3                            | 7.64                                  | 100                                  |          |
|             |            | incl. 119.4 | 120.9     | 1.5                            | 16.0                                  |                                      |          |
|             |            | 237.8       | 238.4     | 0.6                            | 2.28                                  | 181                                  |          |
| HGS         | ER17-770   | 7.7         | 8.2       | 0.5                            | 1.56                                  | 6                                    | 450W     |
|             |            | 188.5       | 189.0     | 0.5                            | 1.11                                  | 137                                  |          |
|             |            | 197.3       | 199.3     | 2.0                            | 1.31                                  | 144                                  |          |

| Type | Drill Hole | From<br>(m) | To<br>(m) | Interval<br>(m) <sup>(1)</sup> | Gold Assay<br>(g/t Au) <sup>(2)</sup> | Vertical<br>Depth (m) <sup>(3)</sup> | Zone |
|------|------------|-------------|-----------|--------------------------------|---------------------------------------|--------------------------------------|------|
|      |            | 211.8       | 212.8     | 1.0                            | 2.10                                  | 154                                  |      |
|      |            | 221.5       | 222.0     | 0.5                            | 2.74                                  | 161                                  |      |
|      |            | 237.0       | 238.0     | 1.0                            | 2.30                                  | 173                                  |      |
|      |            | 272.5       | 273.0     | 0.5                            | 2.02                                  | 199                                  |      |
|      |            | 279.0       | 280.0     | 1.0                            | 35.8                                  | 205                                  |      |
|      |            | 290.3       | 291.3     | 1.0                            | 2.30                                  | 213                                  |      |
|      |            | 298.0       | 299.0     | 1.0                            | 1.44                                  | 219                                  |      |
|      |            | 327.7       | 328.2     | 0.5                            | 1.10                                  | 240                                  |      |
|      |            | 475.0       | 476.0     | 1.0                            | 2.80                                  | 349                                  |      |
|      |            | 482.0       | 482.5     | 0.5                            | 1.89                                  | 354                                  |      |
| HGS  | ER17-773   | 6.6         | 7.2       | 0.6                            | 1.23                                  | 6                                    | 450W |
|      |            | 80.9        | 82.2      | 1.3                            | 2.59                                  | 60                                   |      |
|      |            | 86.6        | 92.8      | 6.2                            | 2.70                                  | 66                                   |      |
|      |            | incl. 87.6  | 89.6      | 2.0                            | 8.45                                  |                                      |      |
|      |            | 104.0       | 106.0     | 2.0                            | 1.34                                  | 77                                   |      |
|      |            | 200.8       | 202.3     | 1.5                            | 2.12                                  | 147                                  |      |
|      |            | 229.0       | 230.0     | 1.0                            | 9.04                                  | 168                                  |      |
|      |            | 262.0       | 262.5     | 0.5                            | 31.7                                  | 192                                  |      |

- <sup>1)</sup> Intervals are presented in core length; true width will vary depending on the intersection angle of the hole with the targeted zone. Holes are generally planned to intersect vein structures as close perpendicular as possible and true widths are estimated to be 75%-85% of downhole widths with the exception of holes 770, 773 and 776 from which true width cannot be determined.
- <sup>2)</sup> For known mineralized zones, intervals are based on geological observations and limited compositing of veins. Assays presented are not capped. Intercepts occur within geological confines of major zones but have not been correlated to individual vein domains at this time.
- <sup>3)</sup> Vertical depth is measured from the surface to the mid-point of the reported interval.