

Table 2: Eau Claire: Summary of Drilling Results

Type	Drill Hole	From	To	Interval	Gold Assay	Vertical Depth	Interpreted Zone
		m	m	m ⁽¹⁾	g/t Au ⁽²⁾	m ⁽³⁾	
Infill	ER16-621	159.0	160.0	1.0	3.22	142	450W
		244.9	245.4	0.5	11.2	217	
		265.7	267.2	1.5	20.2	235	
		incl. 266.2	266.7	0.5	49.1		
		279.0	281.0	2.0	9.24	247	
		incl. 279	280.0	1.0	16.4		
Infill	ER16-629	116.7	117.7	1.0	2.46	102	450W
		267.8	269.8	2.0	6.11	232	
		incl. 267.8	268.3	0.5	7.57		
Infill	ER16-632	273.1	277.2	4.1	5.79	256	450W
		incl. 275.1	276.7	1.6	11.9		
Infill	ER16-635	293.1	294.0	0.9	2.15	252	450W
		343.0	343.5	0.5	5.02	295	
		349.6	350.3	0.7	16.0	300	
		386.6	387.8	1.2	7.59	332	
		398.7	399.3	0.6	5.51	342	
extension	ER16-636	283.5	284.1	0.6	2.95	241	450W
		306.9	307.4	0.5	2.84	261	
Infill	ER16-639	285.9	286.4	0.5	12.6	240	450W
		344.2	345.2	1.0	12.4	290	
extension	ER16-640	282.7	283.7	1.0	2.65	234	450W
		300.0	300.7	0.7	3.22	249	
Infill	ER16-642	262.1	263.2	1.1	6.18	215	450W
		incl. 262.1	262.7	0.6	10.6		
		283.2	283.7	0.5	13.4	231	
		333.6	334.1	0.5	12.8	272	
		336.0	340.4	4.4	4.69	275	
		incl. 337.5	338.0	0.5	10.7		
Infill	ER16-644	347.5	349.1	1.6	3.67	284	450W
		89.6	91.4	1.8	2.77	77	
		95.5	97.9	2.4	1.39	82	
		112.1	112.6	0.5	4.20	95	
		116.6	117.6	1.0	8.61	98	
		189.0	191.1	2.1	4.82	159	
Infill	ER16-645	incl. 190.1	190.6	0.5	11.2		450W
		221.2	221.7	0.5	7.46	173	
		310.3	318.0	7.7	2.36	245	
		incl. 316.3	317.4	1.1	8.14		
		346.2	347.9	1.7	14.6	270	

Type	Drill Hole	From	To	Interval	Gold Assay	Vertical Depth	Interpreted Zone
		m	m	m ⁽¹⁾	g/t Au ⁽²⁾	m ⁽³⁾	
		355.0	356.0	1.0	12.4	278	
extension	ER16-646	245.2	250.0	4.8	2.33	200	450W
		287.0	288.0	1.0	1.32	231	
		150.9	153.4	2.5	2.68	119	
Infill	ER16-647	incl. 150.9	151.4	0.5	8.92		450W
		191.0	191.5	0.5	2.69	148	
		199.3	199.9	0.6	11.4	155	
		210.9	211.4	0.5	4.13	163	
Infill	ER16-649	155.4	157.9	2.5	1.40	121	450W
		164.2	165.2	1.0	11.3	126	
		169.7	174.1	4.4	4.94	132	
		incl. 169.7 and 173.6	174.1	0.5	8.40		
Infill	ER16-650	366.2	366.7	0.5	6.84	313	450W
		432.8	433.3	0.5	8.98	368	
		441.5	442.5	1.0	3.15	376	
extension	ER16-651	259.3	260.7	1.4	2.65	218	450W
Infill	ER16-652	85.3	89.8	4.5	1.26	65	450W
Infill	ER16-654	158.2	159.2	1.0	2.75	121	450W
Infill	ER16-655	322.0	324.3	2.3	1.47	262	450W
		327.2	327.7	0.5	8.28	266	
		340.2	340.7	0.5	4.53	276	
		352.9	354.0	1.1	11.5	286	
		incl. 353.5	354.0	0.5	20.0		
		382.1	384.2	2.1	2.85	310	
		incl. 382.1	382.6	0.5	9.71		
extension	ER16-656	73.4	74.2	0.8	3.13	53	450W
extension	ER16-657	242.5	244.5	2.0	1.96	193	450W
extension	ER16-659	28.0	28.5	0.5	1.79	21	450W
		31.0	33.0	2.0	10.6	24	
		incl. 32	33.0	1.0	15.5		
		35.5	36.0	0.5	4.99	26	
		82.9	83.4	0.5	8.16	61	
extension	ER16-660	345.7	346.4	0.7	4.60	329	
extension	ER16-661	60.3	60.8	0.5	1.14	46	450W
		130.0	131.0	1.0	1.50	98	
Infill	ER16-662	305.2	305.9	0.7	6.98	258	450W
		319.5	320.1	0.6	3.14	270	
		354.4	361.5	7.1	17.0	302	
		incl. 358.5	359.2	0.7	54.6		

Type	Drill Hole	From	To	Interval	Gold Assay	Vertical Depth	Interpreted Zone
		m	m	m ⁽¹⁾	g/t Au ⁽²⁾	m ⁽³⁾	
		365.0	366.5	1.5	6.87	309	
		379.0	382.0	3.0	2.26	321	
		incl. 380.0	381.5	1.5	4.30		
extension	ER16-663				NSV		450W
extension	ER16-667	34	34.5	0.5	1.09	24	450W
		65.5	66.0	0.5	4.52	45	

⁽¹⁾ Intervals are presented in core length; true width will vary depending on the intersection angle of the hole with the targeted zone. Holes are generally planned to intersect vein structures as close perpendicular as possible and true widths are estimated to be 75%-85% of downhole widths.

⁽²⁾ For known mineralized zones, intervals are based on geological observations and limited compositing of veins. Assays presented are not capped. Intercepts occur within geological confines of major zones but have not been correlated to individual vein domains at this time.

⁽³⁾ Vertical depth is measured from the surface to the mid-point of the reported interval.

⁽⁴⁾ The intervals included in Table 1 contain a metal content higher than 10 gxm (grams X metre).